

## **Safety Data Sheet**

# 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name	Ethyl acrylate 0.1% pet
Article Number	E-004
Applications	Diagnosis of contact allergy.
Manufacturer	Chemotechnique MB Diagnostics AB Modemgatan 9 SE-235 39 Vellinge Iab@chemotechnique.se
Telephone Fax	+46 (0) 40 466 077 (Monday-Friday 8.00-16.00 GMT+1) +46 (0) 40 466 700

#### 2. HAZARD IDENTIFICATION

#### Health hazards

The objective of applying a hapten on the patient's skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

#### Signs and symptom of exposure

Dermal irritation.

Medical conditions aggravated by exposure Dermatitis.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Classification according to (EC) No. 1272/2008 [EU-GHS/CLP]					
Component	CAS-No.	Content	Classification		
Petrolatum	8009-03-8	99.9%	-		
Ethyl acrylate	140-88-5	0.1%	<ul> <li>Flamm. liquids 2, Acute tox. Oral 4,</li> <li>Acute tox. Inhal. 4, Acute tox. Derm.</li> <li>4, Skin irrit. 2, Eye irrit. 2, Skin sensit.</li> <li>1, Spec. targ. org. tox single exp. 3;</li> <li>H225, H302, H312, H315, H317,</li> <li>H319, H332, H335</li> </ul>		

Classification according to EU Directive 67/548/EEC and 1999/45/EC				
Component	CAS-No.	Content	Classification	
Petrolatum	8009-03-8	99.9%	-	

#### 4. FIRST AID MEASURES

**Emergency and first aid procedures** Obtain medical attention.

#### 5. FIRE-FIGHTING MEASURES\*

#### Suitable extinguish media

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

## For safety reasons unsuitable extinguishing agents Water with full jet.

**Special protective equipment for fire-fighters** Wear self-contained respiratory protective device. Wear fully protective suit.

\*Data is shown for petrolatum only

#### 6. ACCIDENTAL RELEASES MEASURES

Steps to be taken if material is released or spilled Contain and place in a closed container.

#### 7. HANDLING AND STORAGE

**Precautions to be taken in handling and storage** Store dark at 5-8°C. Avoid extended exposure to light. FOR EXTERNAL USE ONLY.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Respiratory protection** Not required.

Ventilation Local exhaust.

#### Protective gloves Disposal gloves.

**Eye protection** Not required with normal use.

#### Work/Hygienic practices

Wash hands after each use.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Ivory White Semi-solid

E-004 Version 5

Odour	Odourless
Melting point*	50-55° C
Boiling point*	No data available
Flash point*	>100°C
Self ignition*	Product does not self ignite.
Danger of explosion*	Product does not present an explosion hazard.
Density*	No data available.
Solubility in/Miscibility with	Insoluble
Water*	

\*Data is shown for petrolatum only

## **10. STABILITY AND REACTIVITY**

### Incompability

May react with strong oxidizing agents.

## Stability

Stable at recommended storage conditions.

## Hazardous byproducts

Combustion may generate CO, CO2 and other oxides.

## Hazardous polymerization

Will not occur.

## 11. TOXICOLOGICAL INFORMATION

No data available.

## 12. ECOLOGICAL INFORMATION

No data available.

## 13. DISPOSAL CONSIDERATIONS

## Waste disposal method

Comply with federal, state/provincial and local regulation.

## 14. TRANSPORT INFORMATION

Not dangerous goods.

## 15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

## 16. OTHER INFORMATION

## Text of H-statements and R-phrases mentioned in Section 3

Flamm. liquids 2 Acute tox. Oral 4 Acute tox. Inhal. 4 Acute tox. Derm. 4 Skin irrit. 2 Eye irrit. 2 Skin sensit. 1 Spec. targ. org. tox single exp. 3	Flammable liquids (Category 2) Acute toxicity, Oral (Category 4) Acute toxicity, Inhalation (Category 4) Acute toxicity, Dermal (Category 4) Skin irritation (Category 2) Eye irritation (Category 2) Skin sensitization (Category 1) Specific target organ toxicity - single
opec. larg. org. lox single exp. 5	exposure (Category 3)
H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
F	Highly flammable
Xn	Harmful
R11	Highly flammable
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed
R36/37/38	Irritating to eyes, respiratory system and skin
R43	May cause sensitization by skin contact

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.