

Safety Data Sheet

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name	SODIUM LAURYL SULFATE 0.25% aq
Article Number	S-018
Applications	Diagnosis of contact allergy.
Manufacturer	Chemotechnique MB Diagnostics AB Modemgatan 9 SE-235 39 Vellinge lab@chemotechnique.se
Telephone	+46 (0) 40 466 077 (Monday-Friday 8.00-16.00 GMT+1)
Fax	+46 (0) 40 466 700

2. HAZARD IDENTIFICATION

Health hazards

The objective of applying a hapten on the patient's skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

Signs and symptom of exposure

Dermal irritation.

Medical conditions aggravated by exposure

Dermatitis.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classification according to (EC) No. 1272/2008 [EU-GHS/CLP]

Component	CAS-No.	Content	Classification
AQUA Purificata	7732-18-5	99.75%	-
SODIUM LAURYL SULFATE	151-21-3	0.25%	Flamm. solids 2, Acute tox. Oral 4, Acute tox. Derm. 3, Skin irrit. 2, Serious eye dam. 1, Spec. targ. org. tox. - single exp. 3; H228, H302, H311, H315, H318, H335

Classification according to EU Directive 67/548/EEC and 1999/45/EC

Component	CAS-No.	Content	Classification
AQUA Purificata	7732-18-5	99.75%	-
SODIUM LAURYL	151-21-3	0.25%	F, Xn, Xi; R11, R21/22, R37/38, R41

SULFATE

4. FIRST AID MEASURES

Emergency and first aid procedures

Obtain medical attention.

5. FIRE-FIGHTING MEASURES*

No data available.

6. ACCIDENTAL RELEASES MEASURES

Steps to be taken if material is released or spilled

Contain and place in a closed container.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage

Store dark at 5-8°C. Avoid extended exposure to light. Store in a well-sealed container. FOR EXTERNAL USE ONLY.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection

Not required.

Ventilation

Local exhaust.

Protective gloves

Disposal gloves.

Eye protection

Not required with normal use.

Work/Hygienic practices

Wash hands after each use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Clear Colorless Liquid

Odour

Odourless

Boiling point*

100°C

Flash point*

>No data available.

Self ignition*

Product does not self ignite.

Danger of explosion*

Product does not present as an explosion hazard.

Density*

1.0 g/cm³

*Data is shown for AQUA Purificata only

10. STABILITY AND REACTIVITY

Incompability

May react with strong oxidizing agents.

Stability

Stable at recommended storage conditions.

Hazardous polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

No data available.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Waste disposal method

Comply with federal, state/provincial and local regulation.

14. TRANSPORT INFORMATION

Not dangerous goods.

15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

16. OTHER INFORMATION

Text of H-statements and R-phrases mentioned in Section 3

Flamm. solids 2
Acute tox. Oral 4
Acute tox. Derm. 3
Skin irrit. 2
Serious eye dam. 1
Spec. targ. org. tox. - single exp. 3

H228
H302
H311
H315
H318
H335
F
Xn

Flammable solids (Category 2)
Acute toxicity, Oral (Category 4)
Acute toxicity, Dermal (Category 3)
Skin irritation (Category 2)
Serious eye damage (Category 1)
Specific target organ toxicity - single exposure (Category 3)
Flammable solid
Harmful if swallowed
Toxic in contact with skin
Causes skin irritation
Causes serious eye damage
May cause respiratory irritation
Flammable
Harmful

Xi	Irritant
R11	Highly flammable
R21/22	Harmful by inhalation and in contact with skin
R37/38	Irritating to respiratory system and skin
R41	Risk of serious damage to eyes

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.