

# **Safety Data Sheet**

# 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name Hydroperoxides of Limonene 0.2% pet

Article Number H-032B

Applications Diagnosis of contact allergy.

Manufacturer Chemotechnique MB Diagnostics AB

Modemgatan 9 SE-235 39 Vellinge

lab@chemotechnique.se

Telephone +46 (0) 40 466 077 (Monday-Friday 8.00-16.00 GMT+1)

Fax +46 (0) 40 466 700

#### 2. HAZARD IDENTIFICATION

#### **Health hazards**

The objective of applying a hapten on the patient's skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

## Signs and symptom of exposure

Dermal irritation.

## Medical conditions aggravated by exposure

Dermatitis.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

# Classification according to (EC) No. 1272/2008 [EU-GHS/CLP]

Component CAS-No. Content Classification

Petrolatum 8009-03-8 99.8% -

Hydroperoxides of 0.2% Flamm. liquids 3, Skin irrit. 2, Skin Limonene sensit. 1, Acute ag. tox. 1, Chron. a

sensit. 1, Acute aq. tox. 1, Chron. aq. tox. 1; H226, H315, H317, H410

Classification according to EU Directive 67/548/EEC and 1999/45/EC

Component CAS-No. Content Classification

Petrolatum 8009-03-8 99.8% -

Hydroperoxides of 0.2% Xi, N; R10, R38, R43, R50/53

Limonene

H-032B Version 1 Revision Date: 2015-11-04 Print Date: 2025-08-10 Page 1/4

## 4. FIRST AID MEASURES

# **Emergency and first aid procedures**

Obtain medical attention.

#### 5. FIRE-FIGHTING MEASURES\*

# Suitable extinguish media

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

# For safety reasons unsuitable extinguishing agents

Water with full jet.

## Special protective equipment for fire-fighters

Wear self-contained respiratory protective device. Wear fully protective suit.

\*Data is shown for petrolatum only

#### 6. ACCIDENTAL RELEASES MEASURES

# Steps to be taken if material is released or spilled

Contain and place in a closed container.

## 7. HANDLING AND STORAGE

# Precautions to be taken in handling and storage

Store dark at 5-8°C. Avoid extended exposure to light. FOR EXTERNAL USE ONLY.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# **Respiratory protection**

Not required.

#### Ventilation

Local exhaust.

## **Protective gloves**

Disposal gloves.

## Eye protection

Not required with normal use.

## Work/Hygienic practices

Wash hands after each use.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Ivory White Semi Solid

Odour Fragrance

Melting point\* 50-55° C

Boiling point\* No data available

H-032B Version 1 Revision Date: 2015-11-04 Print Date: 2025-08-10 Page 2/4

>100°C Flash point\*

Self ignition\* Product does not self ignite.

Danger of explosion\* Product does not present an explosion hazard.

No data available. Density\*

Insoluble Solubility in/Miscibility with

\*Data is shown for petrolatum only

Water\*

10.

# STABILITY AND REACTIVITY

# Incompability

May react with strong oxidizing agents.

# **Stability**

Stable at recommended storage conditions.

# **Hazardous byproducts**

Combustion may generate CO, CO2 and other oxides.

# **Hazardous polymerization**

Will not occur.

#### 11. **TOXICOLOGICAL INFORMATION**

No data available.

#### 12. **ECOLOGICAL INFORMATION**

No data available.

#### 13. **DISPOSAL CONSIDERATIONS**

## Waste disposal method

Comply with federal, state/provincial and local regulation.

#### 14. TRANSPORT INFORMATION

Not dangerous goods.

#### 15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

#### 16. **OTHER INFORMATION**

# Text of H-statements and R-phrases mentioned in Section 3

Flamm. liquids 3 Flammable liquids (Category 3) Skin irrit. 2 Skin irritation (Category 2) Skin sensit. 1 Skin sensitization (Category 1)

H-032B Version 1 Revision Date: 2015-11-04 Print Date: 2025-08-10 Page 3/4 Acute aq. tox. 1 Acute aquatic toxicity (Category 1)
Chron. aq. tox. 1 Chronic aquatic toxicity (Category 1)

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

Xi Irritant

N Dangerous for the environment

R10 Flammable. R38 Irritating to skin.

R43 May cause sensitization by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.

H-032B Version 1 Revision Date: 2015-11-04 Print Date: 2025-08-10 Page 4/4