

Safety Data Sheet

IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE 1. **COMPANY/UNDERTAKING**

Product Name Beryllium(II)sulfate tetrahydrate 1.0% pet

B-044 Article Number

Applications Diagnosis of contact allergy.

Manufacturer Chemotechnique MB Diagnostics AB

> Modemgatan 9 SE-235 39 Vellinge

lab@chemotechnique.se

+46 (0) 40 466 077 (Monday-Friday 8.00-16.00 GMT+1) Telephone

Fax +46 (0) 40 466 700

2. HAZARD IDENTIFICATION

Health hazards

The objective of applying a hapten on the patient's skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

Signs and symptom of exposure

Dermal irritation.

Medical conditions aggravated by exposure

Dermatitis.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classification according to (EC) No. 1272/2008 [EU-GHS/CLP]

Component CAS-No. Content Classification 99.0% Petrolatum 8009-03-8

7787-56-6 1.0% Beryllium(II)sulfate

Acute tox. Oral 3, Acute tox. Inhal. 2, tetrahydrate

Skin irrit. 2, Eye irrit. 2, Skin sensit. 1, Carc. Inhal. 1B, Spec. targ. org. tox. single exp. 3, Spec. targ. org. tox. rep. exp. 1, Chron. aq. tox. 1; H301, H315, H317, H319, H330, H335,

H350i, H372, H411

Classification according to EU Directive 67/548/EEC and 1999/45/EC Component CAS-No. Content Classification

B-044 Version 1 Revision Date: 2015-11-23 Print Date: 2025-12-07 Page 1/4 Petrolatum
Beryllium(II)sulfate
tetrahydrate

8009-03-8 99.0% 7787-56-6 1.0%

T+, T, Xi, N; R49, R26, R25, R48/23, R36/37/38, R43, R51/53

4. FIRST AID MEASURES

Emergency and first aid procedures

Obtain medical attention.

5. FIRE-FIGHTING MEASURES*

Suitable extinguish media

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents

Water with full jet.

Special protective equipment for fire-fighters

Wear self-contained respiratory protective device. Wear fully protective suit.

*Data is shown for petrolatum only

6. ACCIDENTAL RELEASES MEASURES

Steps to be taken if material is released or spilled

Contain and place in a closed container.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage

Store dark at 5-8°C. Avoid extended exposure to light. FOR EXTERNAL USE ONLY.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection

Not required.

Ventilation

Local exhaust.

Protective gloves

Disposal gloves.

Eye protection

Not required with normal use.

Work/Hygienic practices

Wash hands after each use.

9. PHYSICAL AND CHEMICAL PROPERTIES

B-044 Version 1 Revision Date: 2015-11-23 Print Date: 2025-12-07 Page 2/4

Appearance Ivory White Semi Solid

Odour Odourless

Melting point* 50-55° C

Boiling point* No data available

Flash point* >100°C

Self ignition* Product does not self ignite.

Danger of explosion* Product does not present an explosion hazard.

Density* No data available.

Solubility in/Miscibility with

Water*

Insoluble

10. STABILITY AND REACTIVITY

Incompability

May react with strong oxidizing agents.

Stability

Stable at recommended storage conditions.

Hazardous byproducts

Combustion may generate CO, CO2 and other oxides.

Hazardous polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

No data available.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Waste disposal method

Comply with federal, state/provincial and local regulation.

14. TRANSPORT INFORMATION

Not dangerous goods.

15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

16. OTHER INFORMATION

B-044 Version 1 Revision Date: 2015-11-23 Print Date: 2025-12-07 Page 3/4

^{*}Data is shown for petrolatum only

Text of H-statements and R-phrases mentioned in Section 3

Acute tox. Oral 3 Acute toxicity, Oral (Category 3)
Acute tox. Inhal. 2 Acute toxicity, Inhalation (Category 2)

Skin irrit. 2 Skin irritation (Category 2)
Eye irrit. 2 Eye irritation (Category 2)
Skin sensit. 1 Skin sensitization (Category 1)

Carc. Inhal. 1B Carcinogenicity, Inhalation (Category 1B)

Spec. targ. org. tox. - single exp. Specific target organ toxicity - single exposure (Category 3)

3

Spec. targ. org. tox. – rep. Specific target organ toxicity - repeated exposure (Category

exp. 1 1)

Chron. aq. tox. 1 Chronic aquatic toxicity (Category 1)

H301 Toxic if swallowed. H315 Causes skin irritation

H317 May cause an allergic skin reaction
H319 Causes serious eye irritation

H330 Fatal if inhaled.

H335 May cause respiratory irritation H350i May cause cancer by inhalation.

H372 Causes damage to organs through prolonged or repeated

exposure.

H411 Toxic to aquatic life with long lasting effects.

T+ Very Toxic
T Toxic
Xi Irritant

N Dangerous for the environment. R49 May cause cancer by inhalation

R26 Very toxic by inhalation R25 Toxic if swallowed

R48/23 Toxic: danger of serious damage to health by prolonged

exposure through inhalation

R36/37/38 Irritating to eyes, respiratory system and skin R43 May cause sensitisation by skin contact

R51/53 Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.

B-044 Version 1 Revision Date: 2015-11-23 Print Date: 2025-12-07 Page 4/4