



## Safety Data Sheet

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name	Nickel(II)sulfate hexahydrate 5.0% pet
Article Number	N-002A
Applications	Diagnosis of contact allergy.
Manufacturer	Chemotechnique MB Diagnostics AB Modemgatan 9 SE-235 39 Vellinge <a href="mailto:lab@chemotechnique.se">lab@chemotechnique.se</a>
Telephone	+46 (0) 40 466 077 (Monday-Friday 8.00-16.00 GMT+1)
Fax	+46 (0) 40 466 700

### 2. HAZARD IDENTIFICATION

#### Health hazards

The objective of applying a hapten on the patient's skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

#### Signs and symptom of exposure

Dermal irritation.

#### Medical conditions aggravated by exposure

Dermatitis.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Classification according to (EC) No. 1272/2008 [EU-GHS/CLP]

Component	CAS-No.	Content	Classification
Petrolatum	8009-03-8	95.0%	-
Nickel(II)sulfate hexahydrate	10101-97-0	5.0%	Carc. 2, Resp. sensit. 1, Skin sensit. 1, Acute aq. tox. 1, Chron. aq. tox. 1, Acute tox. Oral 4; H302, H317, H334, H351, H410

#### Classification according to EU Directive 67/548/EEC and 1999/45/EC

Component	CAS-No.	Content	Classification
Petrolatum	8009-03-8	95.0%	-
Nickel(II)sulfate hexahydrate	10101-97-0	5.0%	Xn,N; R22, R40, R42/43, R50/53

#### 4. FIRST AID MEASURES

##### Emergency and first aid procedures

Obtain medical attention.

#### 5. FIRE-FIGHTING MEASURES\*

##### Suitable extinguish media

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

##### For safety reasons unsuitable extinguishing agents

Water with full jet.

##### Special protective equipment for fire-fighters

Wear self-contained respiratory protective device. Wear fully protective suit.

\*Data is shown for petrolatum only

#### 6. ACCIDENTAL RELEASES MEASURES

##### Steps to be taken if material is released or spilled

Contain and place in a closed container.

#### 7. HANDLING AND STORAGE

##### Precautions to be taken in handling and storage

Store dark at 5-8°C. Avoid extended exposure to light. FOR EXTERNAL USE ONLY.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

##### Respiratory protection

Not required.

##### Ventilation

Local exhaust.

##### Protective gloves

Disposal gloves.

##### Eye protection

Not required with normal use.

##### Work/Hygienic practices

Wash hands after each use.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Green Semi-solid

Odour Odourless

Melting point\* 50-55° C

Boiling point*	No data available
Flash point*	>100°C
Self ignition*	Product does not self ignite.
Danger of explosion*	Product does not present an explosion hazard.
Density*	No data available.
Solubility in/Miscibility with Water*	Insoluble

\*Data is shown for petrolatum only

## 10. STABILITY AND REACTIVITY

### Incompability

May react with strong oxidizing agents.

### Stability

Stable at recommended storage conditions.

### Hazardous byproducts

Combustion may generate CO, CO<sub>2</sub> and other oxides.

### Hazardous polymerization

Will not occur.

## 11. TOXICOLOGICAL INFORMATION

No data available.

## 12. ECOLOGICAL INFORMATION

No data available.

## 13. DISPOSAL CONSIDERATIONS

### Waste disposal method

Comply with federal, state/provincial and local regulation.

## 14. TRANSPORT INFORMATION

Not dangerous goods.

## 15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

## 16. OTHER INFORMATION

### Text of H-statements and R-phrases mentioned in Section 3

Carc. 2.  
Resp. sensit. 1

Carcinogenicity (Category 2)  
Respiratory sensitization (Category 1)

Skin sensit. 1	Skin sensitization (Category 1)
Acute aq. tox. 1	Acute aquatic toxicity (Category 1)
Chron. aq. tox. 1	Chronic aquatic toxicity (Category 1)
Acute tox. Oral 4	Acute toxicity, Oral (Category 4)
H302	Harmful if swallowed
H317	May cause an allergic skin reaction
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H351	Suspected of causing cancer
H410	Very toxic to aquatic life with long lasting effects
Xn	Harmful
N	Dangerous for the environment
R22	Harmful if swallowed
R40	Limited evidence of a carcinogenic effect
R42/43	May cause sensitization by inhalation and skin contact
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.