Safety Data Sheet

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name	2-n-Octyl-4-isothiazolin-3-one 0.1% pet
Article Number	O-004
Applications	Diagnosis of contact allergy.
Manufacturer	Chemotechnique MB Diagnostics AB Modemgatan 9 SE-235 39 Vellinge lab@chemotechnique.se
Telephone Fax	+46 (0) 40 466 077 (Monday-Friday 8.00-16.00 GMT+1) +46 (0) 40 466 700

2. HAZARD IDENTIFICATION

Health hazards
The objective of applying a hapten on the patient´s skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

Signs and symptom of exposure
Dermal irritation.

Medical conditions aggravated by exposure
Dermatitis.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classification according to (EC) No. 1272/2008 [EU-GHS/CLP]

Component	CAS-No.	Content	Classification
Petrolatum	8009-03-8	99.9%	-
2-n-Octyl-4-isothiazolin-3-one	26530-20-1	0.1%	Acute tox. Inhal. 3, Acute tox. Derm. 3, Acute tox. Oral 4, Skin corr. 1B, Skin sensit. 1, Acute aq. tox. 1, Chron. aq. tox. 1, H302, H311, H314, H317, H331, H410

Classification according to EU Directive 67/548/EEC and 1999/45/EC

Component	CAS-No.	Content	Classification
Petrolatum	8009-03-8	99.9%	-
2-n-	26530-20-1	0.1%	T, C, N; R22, R23/24, R34,

4. FIRST AID MEASURES

Emergency and first aid procedures
Obtain medical attention.

5. FIRE-FIGHTING MEASURES*

Suitable extinguish media
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents
Water with full jet.

Special protective equipment for fire-fighters
Wear self-contained respiratory protective device. Wear fully protective suit.

*Data is shown for petrolatum only

6. ACCIDENTAL RELEASES MEASURES

Steps to be taken if material is released or spilled
Contain and place in a closed container.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage
Store dark at 5-8°C. Avoid extended exposure to light. FOR EXTERNAL USE ONLY.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection
Not required.

Ventilation
Local exhaust.

Protective gloves
Disposal gloves.

Eye protection
Not required with normal use.

Work/Hygienic practices
Wash hands after each use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Ivory white Semi-solid
Odour	Odourless

Melting point*	50-55° C
Boiling point*	No data available
Flash point*	>100°C
Self ignition*	Product does not self ignite.
Danger of explosion*	Product does not present an explosion hazard.
Density*	No data available.
Solubility in/Miscibility with Water*	Insoluble

*Data is shown for petrolatum only

10. STABILITY AND REACTIVITY

Incompability
May react with strong oxidizing agents.

Stability
Stable at recommended storage conditions.

Hazardous byproducts
Combustion may generate CO, CO2 and other oxides.

Hazardous polymerization
Will not occur.

11. TOXICOLOGICAL INFORMATION

No data available.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Waste disposal method
Comply with federal, state/provincial and local regulation.

14. TRANSPORT INFORMATION

Not dangerous goods.

15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

16. OTHER INFORMATION

Text of H-statements and R-phrases mentioned in Section 3

Acute tox. Inhal. 3	Acute toxicity, Inhalation (Category 3)
Acute tox. Derm. 3	Acute toxicity, Dermal (Category 3)
Acute tox. Oral 4	Acute toxicity, Oral (Category 4)
Skin corr. 1B	Skin corrosion (Category 1B)
Skin sensit. 1	Skin sensitization (Category 1)
Acute aq. tox. 1	Acute aquatic toxicity (Category 1)
Chron. aq. tox. 1	Chronic aquatic toxicity (Category 1)
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H331	Toxic if inhaled
H410	Very toxic to aquatic life with long lasting effects
T	Toxic
C	Corrosive
N	Dangerous to the environment
R22	Harmful if swallowed
R23/24	Toxic by inhalation and in contact with skin
R34	Causes burns
R43	May cause sensitization by skin contact
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.