

## Safety Data Sheet

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name 4-tert-Butylcatechol 0.25% pet  
Article Number B-030B  
Applications Diagnosis of contact allergy.  
Manufacturer Chemotechnique MB Diagnostics AB  
Modemgatan 9  
SE-235 39 Vellinge  
[lab@chemotechnique.se](mailto:lab@chemotechnique.se)  
Telephone +46 (0) 40 466 077 (Monday-Friday 8.00-16.00 GMT+1)  
Fax +46 (0) 40 466 700

### 2. HAZARD IDENTIFICATION

#### Health hazards

The objective of applying a hapten on the patient's skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

#### Signs and symptom of exposure

Dermal irritation.

#### Medical conditions aggravated by exposure

Dermatitis.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Classification according to (EC) No. 1272/2008 [EU-GHS/CLP]

Component	CAS-No.	Content	Classification
Petrolatum	8009-03-8	99.75%	-
4-tert-Butylcatechol	98-29-3	0.25%	Acute tox. Oral 4, Acute tox. Derm.3, Skin corr. 1B, Skin sensit. 1, Chron. aq. tox. 2; H302, H311, H314, H317, H411

#### Classification according to EU Directive 67/548/EEC and 1999/45/EC

Component	CAS-No.	Content	Classification
Petrolatum	8009-03-8	99.75%	-
4-tert-Butylcatechol	98-29-3	0.25%	C, N; R21/22, R34, R43, R51/53

#### 4. FIRST AID MEASURES

##### **Emergency and first aid procedures**

Obtain medical attention.

#### 5. FIRE-FIGHTING MEASURES\*

##### **Suitable extinguish media**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

##### **For safety reasons unsuitable extinguishing agents**

Water with full jet.

##### **Special protective equipment for fire-fighters**

Wear self-contained respiratory protective device. Wear fully protective suit.

\*Data is shown for petrolatum only

#### 6. ACCIDENTAL RELEASES MEASURES

##### **Steps to be taken if material is released or spilled**

Contain and place in a closed container.

#### 7. HANDLING AND STORAGE

##### **Precautions to be taken in handling and storage**

Store dark at 5-8°C. Avoid extended exposure to light. FOR EXTERNAL USE ONLY.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

##### **Respiratory protection**

Not required.

##### **Ventilation**

Local exhaust.

##### **Protective gloves**

Disposal gloves.

##### **Eye protection**

Not required with normal use.

##### **Work/Hygienic practices**

Wash hands after each use.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Pale Yellow Semi-solid

Odour

Odourless

Melting point\*

50-55° C

Boiling point\*

No data available

Flash point*	>100°C
Self ignition*	Product does not self ignite.
Danger of explosion*	Product does not present an explosion hazard.
Density*	No data available.
Solubility in/Miscibility with Water*	Insoluble

\*Data is shown for petrolatum only

## 10. STABILITY AND REACTIVITY

### Incompability

May react with strong oxidizing agents.

### Stability

Stable at recommended storage conditions.

### Hazardous byproducts

Combustion may generate CO, CO<sub>2</sub> and other oxides.

### Hazardous polymerization

Will not occur.

## 11. TOXICOLOGICAL INFORMATION

No data available.

## 12. ECOLOGICAL INFORMATION

No data available.

## 13. DISPOSAL CONSIDERATIONS

### Waste disposal method

Comply with federal, state/provincial and local regulation.

## 14. TRANSPORT INFORMATION

Not dangerous goods.

## 15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

## 16. OTHER INFORMATION

### Text of H-statements and R-phrases mentioned in Section 3

Acute tox. Oral 4	Acute toxicity, Oral (Category 4)
Acute tox. Derm. 3	Acute toxicity, Dermal (Category 3)
Skin corr. 1B	Skin corrosion (Category 1B)

Skin sensit. 1	Skin sensitization (Category 1)
Chron. aq. tox. 2	Chronic aquatic toxicity (Category 2)
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H411	Toxic to aquatic life with long lasting effects
C	Corrosive
N	Dangerous to the environment
R21/22	Harmful in contact with skin and if swallowed
R34	Causes burns
R43	May cause sensitization by skin contact
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.