

# **Safety Data Sheet**

# 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

| Product Name     | AMMONIUM PERSULFATE 2.5% pet  |
|------------------|---|
| Article Number   | A-011   |
| Applications     | Diagnosis of contact allergy.   |
| Manufacturer     | Chemotechnique MB Diagnostics AB<br>Modemgatan 9<br>SE-235 39 Vellinge<br>lab@chemotechnique.se |
| Telephone<br>Fax | +46 (0) 40 466 077 (Monday-Friday 8.00-16.00 GMT+1)<br>+46 (0) 40 466 700                       |

### 2. HAZARD IDENTIFICATION

### Health hazards

The objective of applying a hapten on the patient's skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

### Signs and symptom of exposure

Dermal irritation.

Medical conditions aggravated by exposure Dermatitis.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Classification according to (EC) No. 1272/2008 [EU-GHS/CLP] |           |         |  |  |  |
|---|-----------|---------|--|--|--|
| Component   | CAS-No.   | Content | Classification   |  |  |
| Petrolatum  | 8009-03-8 | 97.5%   | -  |  |  |
| AMMONIUM<br>PERSULFATE                                      | 7727-54-0 | 2.5%    | Oxidiz. Sol. 3, Acute tox. Oral 4,<br>Eyeirrit. 2, Spec. targ. org. tox<br>singleexp. 3, Skin irrit. 2, Resp.<br>sensit. 1,Skin sensit. 1; H272, H302, |  |  |
|   |           |         | H315,H317, H319, H334, H335  |  |  |

| Classification according to EU Directive 67/548/EEC and 1999/45/EC |           |         |                                    |  |  |
|--|-----------|---------|------------------------------------|--|--|
| Component  | CAS-No.   | Content | Classification                     |  |  |
| Petrolatum   | 8009-03-8 | 97.5%   | -                                  |  |  |
| AMMONIUM   | 7727-54-0 | 2.5%    | O, Xn; R 8, R22, R36/37/38, R42/43 |  |  |

#### 4. **FIRST AID MEASURES**

**Emergency and first aid procedures** Obtain medical attention.

#### 5. **FIRE-FIGHTING MEASURES\***

### Suitable extinguish media

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

### For safety reasons unsuitable extinguishing agents Water with full jet.

Special protective equipment for fire-fighters Wear self-contained respiratory protective device. Wear fully protective suit.

\*Data is shown for petrolatum only

#### **ACCIDENTAL RELEASES MEASURES** 6.

Steps to be taken if material is released or spilled Contain and place in a closed container.

#### 7. HANDLING AND STORAGE

Precautions to be taken in handling and storage Store dark at 5-8°C. Avoid extended exposure to light. FOR EXTERNAL USE ONLY.

#### **EXPOSURE CONTROLS/PERSONAL PROTECTION** 8.

**Respiratory protection** Not required.

Ventilation Local exhaust.

### **Protective gloves**

Disposal gloves.

### Eye protection

Not required with normal use.

### Work/Hygienic practices

Wash hands after each use.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odour

Light Beige Semi-solid Odourless

Page 2/4

Melting point\*50-55° CBoiling point\*No data availableFlash point\*>100°CSelf ignition\*Product does not self ignite.Danger of explosion\*Product does not present an explosion hazard.Density\*No data available.Solubility in/Miscibility withInsolubleWater\*Water\*

\*Data is shown for petrolatum only

### **10. STABILITY AND REACTIVITY**

### Incompability

May react with strong oxidizing agents.

### Stability

Stable at recommended storage conditions.

### Hazardous byproducts

Combustion may generate CO, CO2 and other oxides.

## Hazardous polymerization

Will not occur.

### 11. TOXICOLOGICAL INFORMATION

No data available.

### 12. ECOLOGICAL INFORMATION

No data available.

### 13. DISPOSAL CONSIDERATIONS

### Waste disposal method

Comply with federal, state/provincial and local regulation.

### 14. TRANSPORT INFORMATION

Not dangerous goods.

### 15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

### 16. OTHER INFORMATION

### Text of H-statements and R-phrases mentioned in Section 3

| Oxidiz. Sol. 3<br>Acute tox. Oral 4<br>Eye irrit. 2<br>Spec. targ. org. tox single exp. 3 | Oxidizing solids (Category 3)<br>Acute toxicity, Oral (Category 4)<br>Eye irritation (Category 2)<br>Specific target organ toxicity - single |
|---|--|
| Skin irrit. 2   | exposure (Category 3)<br>Skin irritation (Category 2)  |
| Resp. sensit. 1   | Respiratory sensitization (Category 1)   |
| Skin sensit. 1  | Skin sensitization (Category 1)  |
| H272  | May intensify fire; oxidiser   |
| H302  | Harmful if swallowed   |
| H315  | Causes skin irritation   |
| H317  | May cause an allergic skin reaction  |
| H319  | Causes serious eye irritation  |
| H334  | May cause allergy or asthma symptoms or  |
|   | breathing difficulties if inhaled  |
| H335  | May cause respiratory irritation   |
| 0   | Oxidising  |
| Xn  | Harmful  |
| R 8   | Contact with combustible material may cause  |
|   | fire   |
| R22   | Harmful if swallowed   |
| R36/37/38   | Irritating to eyes, respiratory system and skin  |
| R42/43  | May cause sensitization by inhalation and skin contact   |

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.