

# **Safety Data Sheet**

# 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name	ZINC DIBUTYLDITHIOCARBAMATE (ZBC) 1.0% pet
Article Number	Z-002
Applications	Diagnosis of contact allergy.
Manufacturer	Chemotechnique MB Diagnostics AB Modemgatan 9 SE-235 39 Vellinge lab@chemotechnique.se
Telephone Fax	+46 (0) 40 466 077 (Monday-Friday 8.00-16.00 GMT+1) +46 (0) 40 466 700

#### 2. HAZARD IDENTIFICATION

#### Health hazards

The objective of applying a hapten on the patient's skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

#### Signs and symptom of exposure

Dermal irritation.

Medical conditions aggravated by exposure Dermatitis.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Classification according to (EC) No. 1272/2008 [EU-GHS/CLP]			
Component	CAS-No.	Content	Classification
Petrolatum	8009-03-8	99.0%	-
ZINC DIBUTYLDITHIOCA	136-23-2	1.0%	Chron. aq. tox. 1, Eye irrit. 2, Skin irrit.
RBAMATE (ZBC)			2, Skin sensit. 1, Spec. targ. org. tox. - single exp. 3; H315, H317, H319, H335, H410
Classification appording to EU Directive 67/549/EEC and 1000/45/EC			

Classification according to EU Directive 67/548/EEC and 1999/45/EC			
Component	CAS-No.	Content	Classification
Petrolatum	8009-03-8	99.0%	-
ZINC DIBUTYLDITHIOCA RBAMATE (ZBC)	136-23-2	1.0%	Xi, N; R36/37/38, R43, R50/53,

#### 4. FIRST AID MEASURES

**Emergency and first aid procedures** Obtain medical attention.

#### 5. FIRE-FIGHTING MEASURES\*

#### Suitable extinguish media

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents Water with full jet.

**Special protective equipment for fire-fighters** Wear self-contained respiratory protective device. Wear fully protective suit.

\*Data is shown for petrolatum only

#### 6. ACCIDENTAL RELEASES MEASURES

Steps to be taken if material is released or spilled Contain and place in a closed container.

#### 7. HANDLING AND STORAGE

**Precautions to be taken in handling and storage** Store dark at 5-8°C. Avoid extended exposure to light. FOR EXTERNAL USE ONLY.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection Not required.

Ventilation Local exhaust.

**Protective gloves** Disposal gloves.

**Eye protection** Not required with normal use.

Work/Hygienic practices

Wash hands after each use.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odour Ivory White Semi-solid Odourless

Melting point\*

50-55° C

Z-002 Version 3

Boiling point\*No data availableFlash point\*>100°CSelf ignition\*Product does not self ignite.Danger of explosion\*Product does not present an explosion hazard.Density\*No data available.Solubility in/Miscibility withInsolubleWater\*Water\*

\*Data is shown for petrolatum only

## 10. STABILITY AND REACTIVITY

#### Incompability

May react with strong oxidizing agents.

#### Stability

Stable at recommended storage conditions.

#### Hazardous byproducts

Combustion may generate CO, CO2 and other oxides.

# Hazardous polymerization

Will not occur.

## 11. TOXICOLOGICAL INFORMATION

No data available.

## 12. ECOLOGICAL INFORMATION

No data available.

## 13. DISPOSAL CONSIDERATIONS

#### Waste disposal method

Comply with federal, state/provincial and local regulation.

## 14. TRANSPORT INFORMATION

Not dangerous goods.

#### 15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

#### 16. OTHER INFORMATION

#### Text of H-statements and R-phrases mentioned in Section 3

Acute aq. tox. 1		Acute aquatic toxicity (Category 1)		
Eye irrit. 2		Eye irritation (Category 2)		
Z-002 Version 3	Revision Date: 2014-09-09	Print Date: 2025-06-21	Page 3/4	

Skin irrit. 2 Skin sensit. 1 Spec. targ. org. tox single exp. 3	Skin irritation (Category 2) Skin sensitization (Category 1) Specific target organ toxicity - single
1945	exposure (Category 3)
H315 H317	Causes skin irritation. May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H410	Very toxic to aquatic life with long lasting
	effects.
Xi	Irritant
Ν	Dangerous for the environment.
R36/37/38	Irritating to eyes, respiratory system and skin.
R43	May cause sensitisation by skin contact.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.