

Safety Data Sheet

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name PROPIONIC ACID 3.0% pet

Article Number P-018

Applications Diagnosis of contact allergy.

Manufacturer Chemotechnique MB Diagnostics AB

Modemgatan 9 SE-235 39 Vellinge

lab@chemotechnique.se

Telephone +46 (0) 40 466 077 (Monday-Friday 8.00-16.00 GMT+1)

Fax +46 (0) 40 466 700

2. HAZARD IDENTIFICATION

Health hazards

The objective of applying a hapten on the patient's skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

Signs and symptom of exposure

Dermal irritation.

Medical conditions aggravated by exposure

Dermatitis.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classification according to (EC) No. 1272/2008 [EU-GHS/CLP]

Component CAS-No. Content Classification

Petrolatum 8009-03-8 97.0%

PROPIONIC ACID 79-09-4 3.0% Flamm. liquids 3, Skin corr. 1B;

H226, H314

Classification according to EU Directive 67/548/EEC and 1999/45/EC

Component CAS-No. Content Classification

Petrolatum 8009-03-8 97.0% -

PROPIONIC ACID 79-09-4 3.0% C; R10, R34

P-018 Version 3 Revision Date: 2014-09-09 Print Date: 2024-05-20 Page 1/4

4. FIRST AID MEASURES

Emergency and first aid procedures

Obtain medical attention.

5. FIRE-FIGHTING MEASURES*

Suitable extinguish media

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents

Water with full jet.

Special protective equipment for fire-fighters

Wear self-contained respiratory protective device. Wear fully protective suit.

*Data is shown for petrolatum only

6. ACCIDENTAL RELEASES MEASURES

Steps to be taken if material is released or spilled

Contain and place in a closed container.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage

Store dark at 5-8°C. Avoid extended exposure to light. FOR EXTERNAL USE ONLY.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection

Not required.

Ventilation

Local exhaust.

Protective gloves

Disposal gloves.

Eye protection

Not required with normal use.

Work/Hygienic practices

Wash hands after each use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Ivory White Semi-solid

Odour Odourless

Melting point* 50-55° C

Boiling point* No data available

Flash point* >100°C

P-018 Version 3 Revision Date: 2014-09-09 Print Date: 2024-05-20 Page 2/4

Self ignition* Product does not self ignite.

Danger of explosion* Product does not present an explosion hazard.

Density* No data available.

Solubility in/Miscibility with Insoluble

Water*

10. STABILITY AND REACTIVITY

Incompability

May react with strong oxidizing agents.

Stability

Stable at recommended storage conditions.

Hazardous byproducts

Combustion may generate CO, CO2 and other oxides.

Hazardous polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

No data available.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Waste disposal method

Comply with federal, state/provincial and local regulation.

14. TRANSPORT INFORMATION

Not dangerous goods.

15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

16. OTHER INFORMATION

Text of H-statements and R-phrases mentioned in Section 3

Flamm. liquids 3 Flammable liquids (Category 3)
Skin corr. 1B Skin corrosion (Category 1B)
H226 Flammable liquid and vapour

H314 Causes severe skin burns and eye damage

P-018 Version 3 Revision Date: 2014-09-09 Print Date: 2024-05-20 Page 3/4

^{*}Data is shown for petrolatum only

C Corrosive R10 Flammable R34 Causes burn

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.

P-018 Version 3 Revision Date: 2014-09-09 Print Date: 2024-05-20 Page 4/4