

SAFETY DATA SHEET

Mx-01

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name Thiuram mix 1.0% pet

Article Number Mx-01

Applications Diagnosis of contact allergy.

Manufacturer Chemotechnique MB Diagnostics AB

Modemgatan 9 SE-235 39 Vellinge

Telephone +46 (0) 40 466 077 (Monday-Friday 8.00-16.00)

Fax +46 (0) 40 466 700

2. HAZARD IDENTIFICATION

Health hazards

The objective of applying a hapten on the patient's skin is the diagnosis of contact allergy. Localized dermal allergic reaction may occur at test site.

Signs and symptom of exposure

Dermal irritation.

Medical conditions aggravated by exposure

Dermatitis.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classification according to (EC) No. 1272/2008 [EU-GHS/CLP] Component CAS-No. **Content Classification** Petrolatum 8009-03-8 99.0% Tetramethylthiuram 97-74-5 0.25% Skin sens. 1, Chron. aq. tox. 2, monosulfide (TMTM) Acute tox. Oral 4; H302, H317, H411 Tetramethylthiuram Acute tox., Inhal. 4, Acute tox., Oral 137-26-8 0.25% disulfide (TMTD) 4, Spec. targ. org. tox. – rep. exp. 2, Eye irrit. 2, Skin irrit. 2, Skin sens. 1, Acute aq. tox. 1, Chron. aq. tox. 1; H302, H315, H317, H319, H332, H373, H410 Tetraethylthiuram 97-77-8 0.25% Acute tox., Oral 4, Spec. targ. org. disulfide (TETD) tox. - rep. exp. 2, Skin sens. 1, Acute aq. tox. 1, Chron. aq. tox. 1; H373, H302, H317, H410 Dipentamethylenethiur 0.25% Skin irrit. 2, Skin sensit. 1, Eye irrit. 94-37-1 am disulfide (PTD) 2, Spec. targ. org. tox. - single exp. 3; H315, H317, H319, H335

Mx-01 Version 4 Revision Date: 2019-05-06 Print Date: 2019-05-06 Page 1 of 4



For the full text of the H-statements and R-phrases mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

Emergency and first aid procedures

Obtain medical attention.

5. FIRE-FIGHTING MEASURES*

Suitable extinguish media

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. For safety reasons unsuitable extinguishing agents

Water with full jet.

Special protective equipment for fire-fighters

Wear self-contained respiratory protective device. Wear fully protective suit.

*Data is shown for petrolatum only

6. ACCIDENTAL RELEASES MEASURES

Steps to be taken if material is released or spilled

Contain and place in a closed container.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage

Store dark at 2-8°C. Avoid extended exposure to sunlight. FOR EXTERNAL USE ONLY.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection

Not required.

Ventilation

Local exhaust.

Protective gloves

Disposal gloves.

Eye protection

Not required with normal use.

Work/Hygienic practices

Wash hands after each use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Yellow Semi-solid

Odour Odourless

Melting point* 50-55°C

Mx-01 Version 4 Revision Date: 2019-05-06 Print Date: 2019-05-06 Page 2 of 4



Boiling point* No data available

Flash point* >100°C

Self ignition* Product does not self ignite.

Danger of explosion* Product does not present an explosion hazard.

Density* No data available.

Solubility in/Miscibility with Water* Insoluble

10. STABILITY AND REACTIVITY

Incompability

May react with strong oxidizing agents.

Stability

Stable at recommended storage conditions.

Hazardous byproducts

Combustion may generate CO, CO₂ and other oxides.

Hazardous polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

No data available.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Waste disposal method

Comply with federal, state/provincial and local regulation.

14. TRANSPORT INFORMATION

Not dangerous goods.

15. REGULATORY INFORMATION

The classification is according to the latest editions of the EU lists, and extended by company and literature data.

16. OTHER INFORMATION

Text of H-statements and R-phrases mentioned in Section 3

Skin sens. 1 Skin sensitization (Category 1)
Chron. aq. tox. 2 Chronic aquatic toxicity (Category 2)
Acute tox. Oral 4 Acute toxicity, Oral (Category 4)
Acute tox., Inhal. 4 Acute toxicity, Inhalation (Category 4)

Mx-01 Version 4 Revision Date: 2019-05-06 Print Date: 2019-05-06 Page 3 of 4

^{*}Data is shown for petrolatum only



Spec. targ. Org. tox. - rep. exp. Specific target organ toxicity - repeated exposure (Category

2

Eye irrit. 2 Eye irritation (Category 2) Skin irrit. 2 Skin irritation (Category 2)

Acute aq. tox. 1 Acute aquatic toxicity (Category 1)
Chron. aq. tox. 1 Chronic aquatic toxicity (Category 1)

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated

exposure.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

Pharmaceutical quality of tested hapten is confirmed by Chemotechnique Diagnostics according to validated analytical methods. Hapten passed test according to GMP standards.

Chemotechnique Diagnostics makes no representation as to the comprehensiveness or correctness of the information provided. It is intended only as a guide to a properly trained individual in the appropriate handling of the material.

Mx-01 Version 4 Revision Date: 2019-05-06 Print Date: 2019-05-06 Page 4 of 4